



# ANTENNA SOLUTIONS FOR INTELLIGENT TRANSPORTATION SYSTEMS



## Public Safety / Emergency Response

Optimize communications to keep first responders safe. Ensure connectivity, interoperability, and real-time access to voice, data, video, and text tools with rugged, reliable antennas for mission critical applications.

### GNSS / CELLULAR / WiFi

#### Trooper™



#### Trooper™ II



#### Trooper™ TRP-20INT



### LMR / TETRA / P25

#### Wide Spectrum



### CELLULAR / WiFi / BLUETOOTH® / LMR

#### MLPV



### WiFi / BLUETOOTH®

#### Hush



### CELLULAR / WiFi / BLUETOOTH®

#### GNSMB-COV



# RELIABLE CONNECTIVITY WHEN YOU NEED IT MOST

## Antenna Solutions for Police Vehicles



Featured Platform(s)	Description Title	Mounting Location	Frequency Ranges	Ports	Color
<b>GNSS / CELLULAR / WiFi</b>					
<b>Trooper™</b>	Trooper™ Multiband LTE MIMO & 802.11ac Antennas with High Rejection GPS/GLONASS, Compact Footprint	Roof Exterior*	600 MHz - 6 GHz 2.4 - 2.5 GHz 4.9 - 5.9 GHz 1565 - 1608 MHz	2-in-1 (2 LTE) 3-in-1 (2 LTE + 1 GNSS) 5-in-1 (2 LTE + 2 WiFi + 1 GNSS) 6-in-1 (2 LTE + 3 WiFi + 1 GNSS)	Black or White
<b>Trooper™ II</b>	Trooper™ II Slender Dual Carrier GNSS Multiband Antenna	Roof Exterior*	600 MHz - 6 GHz 2.4 - 2.5 GHz 4.9 - 5.9 GHz 1565 - 1608 MHz	9-in-1 (4 LTE + 4 WiFi + 1 GNSS)	Black or White
<b>Trooper™ TRP-20INT</b>	Multiband LTE MIMO & 802.11ac Antennas with High Rejection GPS/GLONASS	Roof Exterior*	600 MHz - 6 GHz 2.4 - 2.5 GHz 4.9 - 5.9 GHz 1565 - 1608 MHz	2-in-1 (1 WiFi + 1 GNSS) 3-in-1 (2 LTE + 1 GNSS) 5-in-1 (2 LTE + 2 WiFi + 1 GNSS) 6-in-1 (2 LTE + 3 WiFi + 1 GNSS)	Black
<b>LMR / TETRA / P25</b>					
<b>Wide Spectrum</b>	Ultra-Flexible Wide Spectrum Multiband Antenna	Roof Exterior	136 - 174 MHz 380 - 520 MHz 698 - 960 MHz		Black
<b>CELLULAR / WiFi / BLUETOOTH® / LMR</b>					
<b>MLPV</b>	Low Profile Whipless Multiband Antennas	Roof Exterior*	380 - 410 MHz 406 - 430 MHz 430 - 450 MHz 698 - 3800 MHz 618 MHz - 6 GHz 2.4 GHz / 5 GHz		Black or White
<b>CELLULAR / WiFi / BLUETOOTH®</b>					
<b>GNSMB-COV</b>	Ultra Low Profile Multiband MIMO Antenna with High Rejection GNSS	Dashboard	690 - 960 MHz 1710 - 2170 MHz 2300 - 2700 MHz 2.4 - 2.495 GHz 4.91 - 5.825 GHz 1561 - 1608 MHz	3-in-1 (2 LTE + 1 GNSS) 4-in-1 (2 LTE + 1 WiFi + 1 GNSS)	Black
<b>WiFi / BLUETOOTH®</b>					
<b>Hush</b>	Hush Covert WiFi Glass Mount Antennas	Windshield*	2.3 - 2.5 GHz 4.9 - 5.99 GHz		Black

\* Contact us for additional mounting options.

**Let our team design your next project. For more information on Antenna Solutions for Intelligent Transportation Systems, contact NEWCOM.**

**781.826.7989 ▪ sales@newcomglobal.com**

**www.NEWCOMGlobal.com**



PCTEL, Inc.

