

# SAMSUNG

## Make a bold statement, faster

Power on an awe-inspiring viewing experience with The Wall All-In-One. Engineered to be quickly ready to go out of the box, Samsung's most advanced and stunning display makes a bold statement in any environment. With the Wall All-In-One you simply choose your size and resolution, and you're assured of a complete, easy-to-install, brilliant solution.



### Stunning Picture Quality

#### Deeper blacks, greater contrast

Purer black levels with enhanced depth deliver unparalleled contrast and immaculate detail.

#### Vivid, vibrant color purity

With Ultra Chroma Technology, colors leap to life with spectacular vibrancy.

#### Colors mapped to perfection

The Wall All-In-One's 20-bit processing delivers accurate color mapping, for incredibly realistic images.

#### Continuous natural shading

Deeper bit depth at low grayscale and a precise linear grayscale deliver greater contrast ratio and exceptionally smooth, natural tones and shadows.

#### Instant AI optimization

The powerful AI processor delivers enhanced, noise-free visuals in up to 4K resolution.<sup>1</sup>

#### Smooth motion, dazzling dynamic range

The Wall All-In-One automatically converts 60Hz signals to 120Hz for smoother motion graphics. HDR10/10+ and LED HDR illuminate ideal peak brightness and contrast scene-by-scene for spectacular imagery.



### Flexible Design & Installation

#### Pre-Assembled for an Easy Install

The Wall All-In-One drastically simplifies installation with preconfigured modules and docking background plates.<sup>2</sup> Two people can install it in about two hours.<sup>3</sup>

#### Integrated S-Box

Integrated box eliminates cumbersome configuration process and saves space.

#### All-In-One means no extras needed

From the control box and wall brackets to speakers and deco bezels, everything you need to get started is included.



### Easy Management & Security

#### Smarter collaboration with Smart View+

Smart View+ lets you mirror up to four devices of any brand simultaneously for easy collaboration.

#### Flexible video conferencing

The Wall All-In-One supports seamless video conferencing, with Cisco Webex compatibility and Logitech plug-and-play camera capability.<sup>4</sup>

#### Operate with peace of mind

The integrated Knox security platform protects against external attacks, blocks malicious code execution and controls USB and network exchange.

## The Wall All-In-One IAB Series Displays




# The Wall All-In-One IAB Series Displays

Specifications		IA008B: 146" 4K	IA016B: 146" 2K	IA012B: 110" 2K
Physical Parameters	Model Name	IA008B: 146" 4K	IA016B: 146" 2K	IA012B: 110" 2K
	Pixel Pitch	0.84 mm	1.68 mm	1.26 mm
	Pixel Configuration	1 red, 1 green, 1 blue	1 red, 1 green, 1 blue	1 red, 1 green, 1 blue
	Configuration (LxH, per screen)	3840 x 2160 pixels	1920 x 1080 pixels	1920 x 1080 pixels
	Diode Type	Flip-chip RGB LED	Flip-chip RGB LED	Flip-chip RGB LED
	Diagonal (Diagonal x D, per screen)	145.7" x 1.9"	145.7" x 1.9"	109.3" x 1.9"
	Dimensions (W x H x D, screen)	127" x 71.4" x 1.9" / 3,225.6 x 1,814.4 x 49 mm	127" x 71.4" x 1.9" / 3,225.6 x 1,814.4 x 49 mm	95.2" x 53.6" x 1.9" / 2,419.2 x 1,360.8 x 49 mm
	No. of Modules (W x H, per screen)	16 x 12	16 x 12	12 x 9
Optical Parameters	Weight (per screen)	370.4 lbs. / 168 kg	370.4 lbs. / 168 kg	238.1 lbs. / 108 kg (TBD)
	Brightness (Peak/Max) <sup>5</sup>	1,600 nit / 500 nit	1,400 nit / 500 nit	1,600 nit / 500 nit
	Contrast Ratio <sup>6</sup>	24,000:1	22,000:1	24,000:1
	HDR Compatibility	LED HDR / HDR10+ support / AI Picture	LED HDR / HDR10+ support / AI Picture	LED HDR / HDR10+ support / AI Picture
	Viewing Angle (Horizontal / Vertical)	170° / 155°	170° / 155°	170° / 155°
	Bit Depth	16 bit (Internal processing 20bit)	16 bit (Internal processing 20bit)	16 bit (Internal processing 20bit)
	Color Temperature (Default)	6,500K ± 500K (Floating bin)	6,500K ± 500K (Floating bin)	6,500K ± 500K (Floating bin)
	Color Temperature (Adjustable)	2,800K - 10,000K	2,800K - 10,000K	2,800K - 10,000K
Electrical Parameters	Video Rate	50/60 Hz/100/120 (FRC) Hz	50/60 Hz/100/120 (FRC) Hz	50/60 Hz/100/120 (FRC) Hz
	Input Power Range	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz
	Power Consumption (Max. / Typ.)	1700W/Screen / 1100W/Screen	1240W/Screen / 860W/Screen	1000W/Screen (TBD) / 2080W/Screen (TBD)
	Heat Generation (Max. / Typ.)	5800 BTU/Screen / 3753 BTU/Screen	4231 BTU/Screen / 2934 BTU/Screen	9504 BTU/Screen (TBD) / 7104 BTU/Screen (TBD)
Operational Parameters	Refresh Rate <sup>7</sup>	3,840 Hz	7,680 Hz	3,840 Hz
	Power Redundancy	No	No	No
	Working Temperature / Humidity	32°-104° F / 10%-80%RH	32°-104° F / 10%-80%RH	32°-104° F / 10%-80%RH
	Storage Temperature / Humidity	-4°-113° F / 5%-95%RH	-4°-113° F / 5%-95%RH	-4°-113° F / 5%-95%RH
Connectivity	IP Rating	IP20	IP20	IP20
	LED Lifetime	150,000 hours	150,000 hours	150,000 hours
	Controller	Built-in	Built-in	Built-in
	Input (Video)	DP1.2 (1), HDMI 2.0 (3), USB 2.0 (2)	DP1.2 (1), HDMI 1.4 (3), USB 2.0 (2)	DP1.2 (1), HDMI 1.4 (3), USB 2.0 (2)
Sound	Output	Audio (Stereo Mini Jack) / eARC	Audio (Stereo Mini Jack) / eARC	Audio (Stereo Mini Jack) / eARC
	Wi-Fi / Bluetooth	Yes / Yes	Yes / Yes	Yes / Yes
	External Control	RS232C (in), RJ45	RS232C (in), RJ45	RS232C (in), RJ45
Certifications	Speaker	10W x 2	10W x 2	10W x 2
	Safety	62368-1, 60950-1	62368-1, 60950-1	62368-1, 60950-1
	EMC	Class A	Class A	Class A
Service	Eye Protection	TUV Low Blue Light	TUV Low Blue Light	TUV Low Blue Light
	Service	Front	Front	Front
Features	Operating System	Tizen 6.5	Tizen 6.5	Tizen 6.5
	MagiCINFO	Yes	Yes	Yes
	Sensor	Temperature, Eco Sensor	Temperature, Eco Sensor	Temperature, Eco Sensor
	Other	AI Picture, LED HDR, HDR10/10+, Dynamic Peaking	AI Picture, LED HDR, HDR10/10+, Dynamic Peaking	AI Picture, LED HDR, HDR10/10+, Dynamic Peaking
Accessories	Workspace (Microsoft 365/VMWare/RDP), Auto Source Switching and Recovery, Dicom Simulation Mode, SmartView+ (PC)	Workspace (Microsoft 365/VMWare/RDP), Auto Source Switching and Recovery, Dicom Simulation Mode, SmartView+ (PC)	Workspace (Microsoft 365/VMWare/RDP), Auto Source Switching and Recovery, Dicom Simulation Mode, SmartView+ (PC)	
	Other SW Features	Workspace (Microsoft 365/VMWare/RDP), Auto Source Switching and Recovery, Dicom Simulation Mode, SmartView+ (PC)	Workspace (Microsoft 365/VMWare/RDP), Auto Source Switching and Recovery, Dicom Simulation Mode, SmartView+ (PC)	Workspace (Microsoft 365/VMWare/RDP), Auto Source Switching and Recovery, Dicom Simulation Mode, SmartView+ (PC)
Package	Accessories	Décor Frame, Frame Kit, Buffer parts (18 Modules, 1 T-Con, 1 SMPS)	Décor Frame, Frame Kit, Buffer parts (18 Modules, 1 T-Con, 1 SMPS)	Décor Frame, Frame Kit, Buffer parts (18 Modules, 1 T-Con, 1 SMPS)
	Remote Control	IR Remote Controller	IR Remote Controller	IR Remote Controller
	Box Dimension (inches, WxHxD)	78.7" x 85.1" x 39.4"	78.7" x 85.1" x 39.4"	TBD
Special Installation	Box Dimension (mm, WxHxD)	2,000 x 2,162 x 1,000mm	2,000 x 2,162 x 1,000mm	TBD
	Package Weight (per cabinet)	663.6 lbs. / 301 kg	663.6 lbs. / 301 kg	326.3 lbs. / 148 kg
Special Installation	Other <sup>8</sup>	Side by Side Installation with additional frame kit (up to 4 screens)	Side by Side Installation with additional frame kit (up to 4 screens)	Side by Side Installation with additional frame kit (up to 4 screens)

## Connectivity

- Service
- HDR Data Out
- HDR Data In
- IR
- Stereo Mini Jack
- RS232C In
- HDMI In 2 (eARC)
- HDMI In 1
- DP In
- LAN

IAB Series



Front



Back



Contact **NEWCOM**, trusted **Gold Strategic Partner** of Samsung at

**781-826-7989** or at

**sales@newcomglobal.com.**

**NEWCOMGlobal.com**



**SAMSUNG**

©2022 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. All other brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screen images simulated. Non-metric weights and measurements are approximate. Specifications and designs are subject to change without notice. See [samsung.com](http://samsung.com) for detailed information. Printed in USA. DIGSIG-THEWALL-ALLINONEIAB-DSHT-JUN22T

<sup>1</sup>Upscaling resolution may vary based on the resolution support of individual models. <sup>2</sup>The Wall All-In-One 110-inch model requires three preset modules. The 146-inch model requires four preset modules. <sup>3</sup>Install time estimate based on internal testing. <sup>4</sup>Google Duo compatibility and Logitech plug-and-play available Q4. <sup>5</sup>Peak value according to IDMS (Information Display Measurement Standard). <sup>6</sup>Measured under 10 lux light test condition. Contrast in darkroom exceeds 1000000:1. <sup>7</sup>Referring to visual refresh rate. <sup>8</sup>Optional structure required.