Stratus[®] ftScalable[™] Storage Family

Open fault-tolerant storage platform for high performance applications

Real time data is growing. So it's no surprise that improving data storage recovery and managing data growth is a top priority for organizations. Security and compliance regulations, performance bottlenecks, fast, accurate data recovery, scalability and ensuring data availability are all challenges that need to be addressed to achieve successful data management.

Stratus' ftScalable G4, seamlessly integrated with ftServer is the next generation hybrid storage array that optimizes performance and simplifies data storage and management, while minimizing costs, for an always-on complete availability/storage solution.

It packs maximum performance and availability into an economical, scalable, 2U powerhouse. This high-performance, modular array addresses dedicated, shared, and networked storage requirements allowing you to dynamically configure and grow your system as quickly as needed. Advanced storage capabilities enabled by pooled storage maximize performance and availability of spinning or solid-state based storage. The ftScalable storage array plays an integral role in critical application solutions and serves as a key element in disaster recovery, business continuity and regulatory compliance strategies.

Key benefits

- Manages "hot" and "cold" data storage in real time to deliver storage performance that's comparable to all-flash arrays at a fraction of the price
- Accelerates business processes 3x by automatically virtualizing storage across device types simplifying disk management in heterogeneous environments
- Provides continuous availability in a flexible, high performing array
- Expands up to six shelves with up to 600k IOPS, 144 spindles and 259 terabytes of storage, for business growth and maximum investment protection
- Protects sensitive data with encrypted SSD disk technology

Key features

Increase performance and reduce costs with Real-Time Data Tiering

Autonomically measures data usage, identifies "hot" spots as they occur and continuously moves data to the best tier in real time, even as that data usage pattern changes minute by minute.

Increase cache capacity and IOPs performance with Read Cache

Supports SSD/HDD configurations that dramatically increases the amount of read-cache available to the storage system. Using one or two SSDs in the storage configuration automatically activates the read-cache function which can improve overall performance of read intensive applications and workloads.



Save by purchasing only what you need with Thin Provisioning

Streamlines the tasks of provisioning and modifying volumes, allowing IT managers to respond to data growth as needed. User friendly reporting provides constant feedback on volumes, approaching thresholds, allocation, and over-allocation. IT managers can add storage when needed, easily expanding volumes non-disruptively.

Get 100% dedicated device assignment with LUN Pinning

Allows IT managers to pin certain applications to the high performance tier to assure that mission critical applications are always prioritized on SSDs or high-performance drives.

Improve system up-time and data protection with Quick Rebuilds

Rebuilds only the data that is being used, restoring fault-tolerance with 2-5x the performance of standard rebuild designs.

Accelerate business processes with Pooled Storage

Automatically virtualizes storage across device types and simplifies disk management in heterogeneous environments while enabling a wide array of advanced features, such as thin provisioning, rapid RAID rebuild, and tiering.

Streamline storage management with the Management Console

Includes performance monitoring, a dashboard for provisioning and storage tiering, provisioning reports by volume, wizards for configuration, installation and provisioning and customized views of storage.

Prevent unauthorized access to data with Encryption Drives

Provides data security through full disk encryption with support for Seagate[®] Full Disk Encryption (FDE). Self-encrypting drives encrypt every write operation and decrypt every read operation without user intervention. FDE drives remain fully protected with an encryption key.



24/7/365 Worldwide comprehensive solution services

We diagnose, trouble shoot and resolve problems online. And our fully supported phone-home capabilities will link you directly to our support experts the instant any problems are detected. In addition to our global technical support services, we also provide award winning Professional, Managed and Educational Services.

| System Specifications | |
|-----------------------------------|---|
| Storage System Summary | |
| Chassis configuration | 2U, 24 Small Format Factor (SFF) drives |
| Maximum chassis modules | 6 |
| Maximum disks | 144 |
| Maximum capacity (full array) | 259/115 TB HDD/SSD |
| RAID levels | 1, 5, 6, 10 |
| Host ports | 4 per controller/8 per array |
| Host connectivity | 16 Gb Fibre Channel, 10 Gb Ethernet, or mix-and-match |
| High-performance cache technology | DupliCache; EnviroStor |
| Software | |
| | Auto-Tiering & Snapshot |
| Drive Type | |
| | Please visit www.stratus.com/ftserver/disks for supported disk drives |
| Availability Features | |
| Redundant components | RAID I/O modules; power supplies fans |
| Hot standby spare | Yes |
| Automatic controller failover | Yes |
| Multi-path I/O support | Yes |
| Quick rebuild | Yes |
| Hot-swappable, field serviceable | Drives, RAID I/O modules; power supplies/fans |
| Power and Packaging | |
| Input voltage | 100 - 240 VAC; 50 Hz, 60 Hz 4.5 A max., per unit, 400 W |
| Enclosure dimensions (H x W x D) | 3.5" (2U) x 17.6" x 24.8" (rackmount) |
| Weight (fully loaded) | 53 lbs/24 kg |
| Environmental | RoHS, China RoHS, WEEE |

Specifications and descriptions are summary in nature and subject to change without notice.

Stratus and the Stratus Technologies logo are trademarks or registered trademarks of Stratus Technologies Bermuda Ltd. All other marks are the property of their respective owners. ©2019 Stratus Technologies Bermuda Ltd. All rights reserved. 192008



Contact NEWCOM for ftScalable options and process.

781.826.7989 • sales@newcomglobal.com

newcomglobal.com

